



DEY DISTRIBUTING

MAJOR APPLIANCE PARTS
COMMERCIAL • HVAC
CORPORATE
HEADQUARTERS
VADNAIS HEIGHTS, MN
(800) 397-1339
FAX (800) 728-3391

LENEXA, KS
(888) 729-9339
FAX (877) 642-3399

COON RAPIDS, MN
(763) 786-8107
FAX 786-7595

EAGAN, MN
(952) 890-9358
FAX 890-5774

ST. PAUL, MN
(651) 647-0171
FAX 647-5935

FARGO, ND
(800) 697-7339
FAX (888) 397-3397

URBANDALE, IA
(800) 397-6339
FAX (800) 728-3302

SIoux FALLS, SD
(800) 397-2339
FAX (800) 728-3392

DULUTH, MN
(800) 397-5339
FAX (800) 728-3395

GREEN BAY, WI
(800) 397-4339
FAX (800) 728-3394

WATERLOO, IA
(800) 397-3339
FAX (800) 728-3393

BROOKFIELD, WI
(800) 657-0711
FAX (800) 657-0834

DENVER, CO
(800) 797-8339
FAX (888) 246-6170

OMAHA, NE
(800) 608-7357
FAX (800) 608-7353

LEE'S SUMMIT, MO
(866) 470-6918
FAX (816) 525-1901

DALLAS, TX
(833) 679-0174

CENTER LINE, MI
(833) 679-0179

www.deydistributing.com

Stock Up On... Customer Appreciation Day May 6

WHITE-RODGERS Receive an extra 5% Off!

Even the sale items!

1F86-344

Non Progeammable Thermostat

\$49.⁹⁵ - 5% = \$47.⁴⁵

Single-Stage, Heat-Pump, Heat-Only systems (1 Heat / 1 Cool)

- Easy, One-touch, Accurate Temperature Control ($\pm 1^\circ\text{F}$)
- 2.2 sq. inch Digital Display with Backlight
- 3 Modes: Heat, Cool, Fan
- 24 VAC Heating / Cooling systems or 750 mV Heating system

Compatible With:

- Standard / Conventional Heating and Cooling systems
- Gas, Oil, or Electric Heat with Air Conditioning
- Heat-Pump system
- 1 Heat / 1 Cool, Single-Stage system
- Single-stage (1-2 Transformers)



1E78-140

Non Progeammable Thermostat

\$29.⁹⁵ - 5% = \$28.⁴⁵

The perfect upgrade from mechanical thermostat available as Heat Pump or Single Stage offering economy and value with proven reliability.

1F80-361

Programable Thermostat

\$67.⁹⁵ - 5% = \$64.⁵⁵

Single stage, programmable, hardwired battery thermostat.

- Easy to program
- Electronic accuracy
- Permanent program retention
- Lighted display
- B & O terminals
- Millivolt compatible
- Easy to wire terminal block
- Dimensions: 6.1 "W x 3.8 "H x 1.1 "D



Electrical Specifications: 0 to 30 VAC, 50/60 Hz or D.C. 0.05 to 1.0 Amps (load per terminal) Single stage gas, oil, electric Single stage heat pump Millivolt system.

Thermal Specifications: Setpoint Temperature Range: 45 to 90 F